

Coro LED Range

Exterior Wall Lighting



Coro LED up and down wall lights are available in 3000k LED. They are suitable for highlighting wall features.

To clean this product there is available to order a Stainless steel cleaning kit sold separately KSR3183.



Product Features

- 2 year warranty
- IP44
- Class I
- CRI: Ra80
- 2x3w 3000K LED head
- Marine Grade 316L Stainless Steel Body
- Life Expectancy up to 30,000hrs

Product Code	Product Description	Wattage (W)	CCT (K)	Lumens (lm)	CRI (Ra)	Energy Efficiency Class	Protection Class
KSR1286	Coro LED Round Up and Down Wall Light	2x3w	3000	262	80	A+	I
KSR1287	Coro LED Square Up and Down Wall Light	2x3w	3000	262	80	A+	I

Product Specification

Nominal voltage	220~240VAC		
Operating frequency	50/60Hz		
Circuit Wattage	2x3w		
Circuit Current	ТВС		
Driver mA Rating	ТВС		
PFC	0.9		
In Rush Current	ТВС		
Ambient temperature range	-10°c to +40°c		
IP rating	44		

Construction

Body: 316L Stainless Steel Diffuser: Polycarbonate

Standards

BSEN60598-1:2015 Luminaires – Part 1: General requirements and tests


In Conformity with

LVD Low voltage directive 2014/35/EU


EMC Electromagnetic compatibility directive 2014/30/EU ERP Energy related products directive 2009/125/EC RoHS Restriction of hazardous substances 2011/65/EU

Product Dimensions

KSR1286



KSR1287



KSR Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and KSR may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, KSR Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.