

# Navara X

# IP

LED Anti Corrosive Battens



## Product Information

The Navara X IP anti corrosive battens are suitable for a multitude of applications that require a high IP or IK rating.

They come complete with a 3 year warranty for your peace of mind.

## Product Features

- 3 year warranty
- IP65
- IK10
- High efficiency LED technology
- 4000K LED
- CRI: Ra80
- 110° beam angle
- Dimmable options available
- Instant on
- Range of sizes and wattages
- Can be suspended
- Lighting designers can download photometric data from our website

# Product Specification

Product Code	Product Description	Wattage (W)	CCT (K)	Lumens (lm)	CRI (Ra)	Energy Efficiency Class	Protection Class
KSR9880	Navara X4S-IP65 4ft LED Anti Corrosive	24	4000	3169	80	A++	I
KSR9881	Navara X4T-IP65 4ft LED Anti Corrosive	40	4000	5149	80	A++	I
KSR9882	Navara X5S-IP65 5ft LED Anti Corrosive	36	4000	4382	80	A+	I
KSR9883	Navara X5T-IP65 5ft LED Anti Corrosive	60	4000	6786	80	A+	I
KSR9884	Navara X6S-IP65 6ft LED Anti Corrosive	70	4000	8367	80	A+	I

\*For emergency options add EM after the part number

\*\*for dimming options add DALI, SwitchDim or CFDIM (corridor function) after part number

Technical Data	Navara X4S	Navara X4T	Navara X5S	Navara X5T	Navara X6S
Nominal voltage	200~240VAC	200~240VAC	200~240VAC	200~240VAC	200~240VAC
Operating frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz	50-60Hz
Circuit Wattage	25.1w including Driver	41w including Driver	36.8w including driver	60.2w including driver	68.7w including driver
Circuit Current	0.112A	0.176A	0.160A	0.256A	0.294A
Driver Current Rating	500mA	800mA	700mA	1150mA	1400mA
PFC	0.95	0.98	0.98	0.98	0.98
In Rush Current	0.494A Max Peak	0.791A Max Peak	0.795A Max Peak	1.16A Max Peak	1.4 Max Peak
Start Time	< 0.5 Sec	< 0.5 Sec	< 0.5 Sec	< 0.5 Sec	< 0.5 Sec
Ambient temperature range	-20°c to +40°c	-20°c to +40°c	-20°c to +40°c	-20°c to +40°c	-20°c to +40°c
IP rating	65	65	65	65	65

## Construction

Body: Polycarbonate  
 Diffuser: Polycarbonate  
 Clips: Stainless Steel

## Standards

BSEN60598-1:2015 Luminaires – Part 1: General requirements and tests

## In Conformity with

LVD Low voltage directive 2014/35/EU  
 EMC Electromagnetic compatibility directive 2014/30/EU  
 ERP Energy related products directive 2009/125/EC  
 RoHS Restriction of hazardous substances 2011/65/EU

# Product Dimensions

**KSR9880**



**KSR9881**



**KSR9882**



**KSR9883**



**KSR9884**



KSR Lighting is constantly developing and improving its products. For this reason, all product descriptions in this data sheet are intended as a general guide, and KSR may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this data sheet present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, KSR Lighting cannot accept any liability arising from the reliance on such data to the extent permitted.